



cantech.com

# 109-07

## PREMIUM SAFE TACK MASKING TAPE



### DESCRIPTION

The 109-07 is our most versatile masking tape. Its special adhesive formula gives this tape characteristics of both rubber and acrylic adhesive. The tape bonds quickly but won't damage surfaces to which it's applied. It can stay on indoor surfaces for over ten days.

### MAIN FEATURES

- Adhesion remains stable over time.
- Removes cleanly even after long application.
- Paper provides excellent conformability and tear resistance.
- Medium quick stick, light adhesion.

### APPLICATIONS

- For use on regular, semi-delicate and delicate surfaces.
- Recommended where the tape needs to be removed up to ten days after application.
- For masking application where UV resistance is required.
- Designed to resist most paint and lacquer.

**LIGHT ADHESION**

**MEDIUM QUICK STICK**

### TECHNICAL DATA

Colour .....	Green
Backing .....	Saturated crepe paper
Adhesive .....	Natural rubber with UV inhibitor
Thickness .....	5.0 mil (0.127mm)
Adhesion to steel .....	18 oz/in (4.98N/25mm)
Tensile strength .....	20 lb/in (87N/25mm)
Elongation .....	7%
Temperature Resistance .....	80°C (176°F) for 30 minutes

### STOCK SIZE

- 18mm x 55m — 48 rolls/case
- 24mm x 55m — 36 rolls/case
- 36mm x 55m — 24 rolls/case
- 48mm x 55m — 24 rolls/case

#### Please note:

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.

