

Jessica Halverson  
Guardian Fall Protection Inc.  
6305 S 231<sup>st</sup> St  
Kent, WA 98032-1872

Intertek Test Report Number:	G102531900CRT-016
Intertek <i>Signed</i> Quote Number (s):	Qu-00688791
Client PO#:	154263
Product Type:	Self-Retracting Lanyard
Product Model:	10915
Type of Testing Entity:	Third Party Testing Laboratory
Test Standard:	ANSI/ASSE Z359.14-2014
Manufacturer's Name and Address:	See Above
Evaluation/Testing Location:	Intertek, 3933 US Rte 11, Cortland NY 13045 **
Date(s) of Testing:	5/4/16-5/6/16

Dear Jessica,

Intertek has completed the evaluation of the self-retracting Lanyard model 10915, to the client specified requirements of American National Standard, Safety Requirements for Self-Retracting Devices for Personal Fall Arrest and Rescue Systems, ANSI/ASSE Z359.14-2014. The test samples were received in pristine condition. The evaluation was performed at Guardian Fall Protection located in Kent, WA on the dates posted below. The results of these tests are as indicated below.

<u>Tests Completed</u>	<u>Test Date</u>	<u>ANSI/ASSE Z359.14-2014,</u> <u>Clause</u>	<u>Pass/Fail</u>
General Requirements	5/4/16	3	PASS
Static Strength	5/6/16	3.1.7 & 4.2.5	PASS
Dynamic Strength (ambient)	5/5/16	3.1.8 & 4.2.3	PASS
Dynamic Performance (ambient)	5/5/16	3.1.9 & 4.2.1	PASS
Dynamic Performance (hot)	5/5/16	3.1.9 & 4.2.8.1	PASS
Dynamic Performance (cold)	5/4/16	3.1.9 & 4.2.8.2	PASS
Dynamic Performance (wet)	5/4/16	3.1.9 & 4.2.8.3	PASS
Markings and instructions	5/4/16	5	PASS

**Please see attached test data for details.**

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report please contact the undersigned at 607-753-6711.

Tested by,



Andrew Rulison  
Associate Engineer/Team Lead  
Performance Group

Reviewed by,



Jason Allen  
Technical Advisor  
Performance Group

\*\* "Intertek Laboratory is ISO/IEC 17025:2005 (CAN-P-4E) accredited by Standards Council of Canada (SCC) with the scope available for review at the following location: <http://www.scc.ca/en/palcan/38>."

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek, Inc.**

3933 US Route 11, Cortland, NY 13045 USA  
Telephone: +1 607-753-6711 Fax: +1 607-756-9891 Web: [www.intertek.com](http://www.intertek.com)



# INTERTEK TEST DATA SHEETS

Page 2 of 9

Client: <u>Guardian Fall Protection</u>	Engineer: <u>Andrew Rulison</u>
Job No.: <u>G102531900</u>	Tested By: <u>Andrew Rulison</u> Date: <u>5/4/16</u>
Product: <u>Self-Retracting Lanyard</u>	Reviewed By: <u>Jason Allen</u> Date: <u>5/6/16</u>
Model No.: <u>10915</u>	Standard: <u>ANSI/ASSE Z359.14-2014</u>
Sample C/N: <u>See Table</u> <b>TRANSCRIBED TEST DATA</b>	

TEST EQUIPMENT							
Used for Test	Description	Manufacturer	Control No.	Model No.	Serial No.	Cal. Date	Cal. Due
X	Drop Test Structure	Guardian	NA	CAT. 3	-	N/A	N/A
X	Test Dead Weight	NA	15064	282 lbs	-	VBU	VBU
X	Test Dead Weight	NA	15065	300 lbs	-	VBU	VBU
X	Load Cell	NA	235107	-	-	4/9/16	4/9/17
X	Condition Chamber	Thermotron	25098	-	-	8/15/15	8/15/16

Section (Test)	Requirement	Results	Compliance																																				
3.1.7 (4.2.5)	<b>Static Strength:</b> (ambient) shall withstand 3,000 lbs. when tested to: - apply a 3,000 lbs. (+60/-0 lbs) load and maintain for 1-minute to the point of SRL line connection to the SRL drum (across the device)	<table> <tr> <td></td><td>Sample: 1</td><td>Sample: 2</td><td>Sample: 3</td></tr> <tr> <td>Withstand the tensile load</td><td>YES</td><td>YES</td><td>YES</td></tr> </table>		Sample: 1	Sample: 2	Sample: 3	Withstand the tensile load	YES	YES	YES	<b>PASS</b>																												
	Sample: 1	Sample: 2	Sample: 3																																				
Withstand the tensile load	YES	YES	YES																																				
3.1.8 (4.2.3)	<b>Dynamic Strength:</b> (ambient) – shall lock and remained locked until released. The test weight shall not touch the ground. The line constituent shall retain tensile strength of 1,000 lbs. after the dynamic strength test.  1. Connect 300 lb. weight. 2. extract enough line for a 4-foot (48-inch) free fall 3. release the test weight 4. evaluate the line strength of the affected area  Perform Residual Tensile Strength following the Dynamic Strength Test, Section 7.1, 7.2, 7.3 or 7.5.	<table> <tr> <td><b>Sample:</b></td><td>Sample: 1</td><td>Sample: 2</td><td>Sample: 3</td></tr> <tr> <td>SN or ID:</td><td>#1</td><td>#2</td><td>#2</td></tr> <tr> <td>SRL Locked:</td><td>YES</td><td>YES</td><td>YES</td></tr> <tr> <td>SRL Remained Locked until released</td><td>YES</td><td>YES</td><td>YES</td></tr> <tr> <td>Test weight touch the ground</td><td>NO</td><td>NO</td><td>NO</td></tr> <tr> <td>Did SRL payload out to full extension</td><td>NO</td><td>NO</td><td>NO</td></tr> <tr> <td>Did load indicator engage</td><td>YES</td><td>YES</td><td>YES</td></tr> <tr> <td>Retain a minimum of 1,000 lbs of residual tensile strength following the test</td><td>YES</td><td>YES</td><td>YES</td></tr> <tr> <td>MAF: (lbs) Ref only:</td><td>1691</td><td>1408</td><td>1219</td></tr> </table>	<b>Sample:</b>	Sample: 1	Sample: 2	Sample: 3	SN or ID:	#1	#2	#2	SRL Locked:	YES	YES	YES	SRL Remained Locked until released	YES	YES	YES	Test weight touch the ground	NO	NO	NO	Did SRL payload out to full extension	NO	NO	NO	Did load indicator engage	YES	YES	YES	Retain a minimum of 1,000 lbs of residual tensile strength following the test	YES	YES	YES	MAF: (lbs) Ref only:	1691	1408	1219	<b>PASS</b>
<b>Sample:</b>	Sample: 1	Sample: 2	Sample: 3																																				
SN or ID:	#1	#2	#2																																				
SRL Locked:	YES	YES	YES																																				
SRL Remained Locked until released	YES	YES	YES																																				
Test weight touch the ground	NO	NO	NO																																				
Did SRL payload out to full extension	NO	NO	NO																																				
Did load indicator engage	YES	YES	YES																																				
Retain a minimum of 1,000 lbs of residual tensile strength following the test	YES	YES	YES																																				
MAF: (lbs) Ref only:	1691	1408	1219																																				

# INTERTEK TEST DATA SHEETS

Client:	Guardian Fall Protection	Engineer:	Andrew Rulison
Job No.:	G102531900	Tested By:	Andrew Rulison
Product:	Self-Retracting Lanyard	Reviewed By:	Jason Allen
Model No.:	10915	Standard:	ANSI/ASSE Z359.14-2014
Sample C/N:	See Table	<b>TRANSCRIBED TEST DATA</b>	

Section (Test)	Requirement	Results	Compliance																																																																																																									
3.1.9 (4.2.1)	<div><b>Dynamic Performance: "AMBIENT"</b><div><div>1. connect 282 lb. weight</div><div>2. extract enough line for a 36-inch free fall per Fig 5 in Test Standard.</div><div>3. release the test weight</div></div><table><thead><tr><th>Sample:</th><th>Sample: 4</th><th>Sample: 5</th><th>Sample: 6</th></tr></thead><tbody><tr><td>Conditioning in: (4 hrs min)</td><td>24 Hr.</td><td>24 Hr.</td><td>24 Hr.</td></tr><tr><td>Payout and retract the line per 3.1.6 following test</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Lock function shall operate per 3.1.2</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Visual indicator shall activate</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Max. Arrest Force: (lbs.) Class A &amp; B &lt; 1,800 lbs.</td><td>953</td><td>802</td><td>835</td></tr><tr><td>Avg Arrest Force (lbs.): Class A &lt;1,350 lbs. Class B &lt; 900 lbs.</td><td>638</td><td>628</td><td>621</td></tr><tr><td>Distance Initial (in): D1</td><td>36"</td><td>36"</td><td>36"</td></tr><tr><td>Distance Final (in): D2</td><td>66 ¼ "</td><td>80"</td><td>84 ½ "</td></tr><tr><td>Arrest Distance (in): D2-D1 Class A &lt; 24-inches Class B &lt; 54-inches</td><td>30 ¼ "</td><td>44"</td><td>48 ½ "</td></tr></tbody></table><table><thead><tr><th>Section 3.1.6: Results of Retraction Testing following DP testing</th><th>Line Extension ( in or cm )</th><th>Sample: 3.1.5 A (#1)</th><th>Sample: 3.1.5 A (#2)</th><th>Sample: 3.1.5 A (#3)</th></tr></thead><tbody><tr><td>(1) Force (lbs) @ 1 ft</td><td>1'</td><td>2.4</td><td>2.2</td><td>2.7</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(2) Force (lbs) @ 20%</td><td>2'</td><td>2.0</td><td>2.9</td><td>3.8</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(3) Force (lbs) @ 40%</td><td>3'</td><td>4.1</td><td>4.2</td><td>6.5</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(4) Force (lbs) @ 60%</td><td>4'</td><td>6.2</td><td>7.1</td><td>7.3</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(5) Force (lbs) @ 80%</td><td>5'</td><td>8.8</td><td>8.2</td><td>9.2</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(6) Force (lbs) @ 100%</td><td>6'</td><td>10.7</td><td>10.0</td><td>10.1</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr></tbody></table></div>		Sample:	Sample: 4	Sample: 5	Sample: 6	Conditioning in: (4 hrs min)	24 Hr.	24 Hr.	24 Hr.	Payout and retract the line per 3.1.6 following test	YES	YES	YES	Lock function shall operate per 3.1.2	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	953	802	835	Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	638	628	621	Distance Initial (in): D1	36"	36"	36"	Distance Final (in): D2	66 ¼ "	80"	84 ½ "	Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	30 ¼ "	44"	48 ½ "	Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)	(1) Force (lbs) @ 1 ft	1'	2.4	2.2	2.7	Retracted length < 24-inches		N/A	N/A	N/A	(2) Force (lbs) @ 20%	2'	2.0	2.9	3.8	Retracted length < 24-inches		N/A	N/A	N/A	(3) Force (lbs) @ 40%	3'	4.1	4.2	6.5	Retracted length < 24-inches		N/A	N/A	N/A	(4) Force (lbs) @ 60%	4'	6.2	7.1	7.3	Retracted length < 24-inches		N/A	N/A	N/A	(5) Force (lbs) @ 80%	5'	8.8	8.2	9.2	Retracted length < 24-inches		N/A	N/A	N/A	(6) Force (lbs) @ 100%	6'	10.7	10.0	10.1	Retracted length < 24-inches		N/A	N/A	N/A	<div>PASS</div>
Sample:	Sample: 4	Sample: 5	Sample: 6																																																																																																									
Conditioning in: (4 hrs min)	24 Hr.	24 Hr.	24 Hr.																																																																																																									
Payout and retract the line per 3.1.6 following test	YES	YES	YES																																																																																																									
Lock function shall operate per 3.1.2	YES	YES	YES																																																																																																									
Visual indicator shall activate	YES	YES	YES																																																																																																									
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	953	802	835																																																																																																									
Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	638	628	621																																																																																																									
Distance Initial (in): D1	36"	36"	36"																																																																																																									
Distance Final (in): D2	66 ¼ "	80"	84 ½ "																																																																																																									
Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	30 ¼ "	44"	48 ½ "																																																																																																									
Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)																																																																																																								
(1) Force (lbs) @ 1 ft	1'	2.4	2.2	2.7																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								
(2) Force (lbs) @ 20%	2'	2.0	2.9	3.8																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								
(3) Force (lbs) @ 40%	3'	4.1	4.2	6.5																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								
(4) Force (lbs) @ 60%	4'	6.2	7.1	7.3																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								
(5) Force (lbs) @ 80%	5'	8.8	8.2	9.2																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								
(6) Force (lbs) @ 100%	6'	10.7	10.0	10.1																																																																																																								
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																								

# INTERTEK TEST DATA SHEETS

Page 4 of 9

Client:	Guardian Fall Protection	Engineer:	Andrew Rulison
Job No.:	G102531900	Tested By:	Andrew Rulison
Product:	Self-Retracting Lanyard	Reviewed By:	Jason Allen
Model No.:	10915	Standard:	ANSI/ASSE Z359.14-2014
Sample C/N:	See Table	<b>TRANSCRIBED TEST DATA</b>	

Section (Test)	Requirement	Results	Compliance																																																																																																											
3.1.9 (4.2.8.1)	<b>Dynamic Performance: "HEAT"</b>  1. connect 282 lb. weight 2. extract enough line for a 36-inch free fall per Fig 5 in Test Standard. 3. release the test weight 4. test within 90 seconds of removing from conditioning																																																																																																													
	<table><tr><td>54 C, 85% RH</td><td>Sample: 7</td><td>Sample: 8</td><td>Sample: 9</td></tr><tr><td>Conditioning in:</td><td>9:00 am</td><td>9:00 am</td><td>9:00 am</td></tr><tr><td>Conditioning out:</td><td>1:40 pm</td><td>1:45 pm</td><td>1:50 pm</td></tr><tr><td>Payout and retract the line per 3.1.6 following test</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Lock function shall operate per 3.1.2</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Visual indicator shall activate</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Max. Arrest Force: (lbs.) Class A &amp; B &lt; 1,800 lbs.</td><td>959</td><td>872</td><td>1043</td></tr><tr><td>Avg Arrest Force (lbs.): Class A &lt; 1,575 lbs. Class B &lt; 1,125 lbs.</td><td>700</td><td>624</td><td>777</td></tr><tr><td>Distance Initial (in): D1</td><td>36"</td><td>36"</td><td>36"</td></tr><tr><td>Distance Final (in): D2</td><td>76 ½ "</td><td>73"</td><td>66"</td></tr><tr><td>Arrest Distance (in): D2-D1 Class A &lt; 24-inches Class B &lt; 54-inches</td><td>40 ½ "</td><td>37"</td><td>30"</td></tr></table>  <table><tr><td>Section 3.1.6: Results of Retraction Testing following DP testing</td><td>Line Extension ( in or cm )</td><td>Sample: 3.1.5 A (#1)</td><td>Sample: 3.1.5 A (#2)</td><td>Sample: 3.1.5 A (#3)</td></tr><tr><td>(1) Force (lbs) @ 1 ft</td><td>1'</td><td>2.2</td><td>1.4</td><td>2.1</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(2) Force (lbs) @ 20%</td><td>2'</td><td>2.6</td><td>4.1</td><td>3.7</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(3) Force (lbs) @ 40%</td><td>3'</td><td>4.1</td><td>3.7</td><td>4.8</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(4) Force (lbs) @ 60%</td><td>4'</td><td>8.0</td><td>7.5</td><td>6.7</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(5) Force (lbs) @ 80%</td><td>5'</td><td>8.2</td><td>8.3</td><td>9.6</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(6) Force (lbs) @ 100%</td><td>6'</td><td>12.0</td><td>8.9</td><td>11.1</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr></table>			54 C, 85% RH	Sample: 7	Sample: 8	Sample: 9	Conditioning in:	9:00 am	9:00 am	9:00 am	Conditioning out:	1:40 pm	1:45 pm	1:50 pm	Payout and retract the line per 3.1.6 following test	YES	YES	YES	Lock function shall operate per 3.1.2	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	959	872	1043	Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	700	624	777	Distance Initial (in): D1	36"	36"	36"	Distance Final (in): D2	76 ½ "	73"	66"	Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	40 ½ "	37"	30"	Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)	(1) Force (lbs) @ 1 ft	1'	2.2	1.4	2.1	Retracted length < 24-inches		N/A	N/A	N/A	(2) Force (lbs) @ 20%	2'	2.6	4.1	3.7	Retracted length < 24-inches		N/A	N/A	N/A	(3) Force (lbs) @ 40%	3'	4.1	3.7	4.8	Retracted length < 24-inches		N/A	N/A	N/A	(4) Force (lbs) @ 60%	4'	8.0	7.5	6.7	Retracted length < 24-inches		N/A	N/A	N/A	(5) Force (lbs) @ 80%	5'	8.2	8.3	9.6	Retracted length < 24-inches		N/A	N/A	N/A	(6) Force (lbs) @ 100%	6'	12.0	8.9	11.1	Retracted length < 24-inches		N/A
54 C, 85% RH	Sample: 7	Sample: 8	Sample: 9																																																																																																											
Conditioning in:	9:00 am	9:00 am	9:00 am																																																																																																											
Conditioning out:	1:40 pm	1:45 pm	1:50 pm																																																																																																											
Payout and retract the line per 3.1.6 following test	YES	YES	YES																																																																																																											
Lock function shall operate per 3.1.2	YES	YES	YES																																																																																																											
Visual indicator shall activate	YES	YES	YES																																																																																																											
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	959	872	1043																																																																																																											
Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	700	624	777																																																																																																											
Distance Initial (in): D1	36"	36"	36"																																																																																																											
Distance Final (in): D2	76 ½ "	73"	66"																																																																																																											
Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	40 ½ "	37"	30"																																																																																																											
Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)																																																																																																										
(1) Force (lbs) @ 1 ft	1'	2.2	1.4	2.1																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
(2) Force (lbs) @ 20%	2'	2.6	4.1	3.7																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
(3) Force (lbs) @ 40%	3'	4.1	3.7	4.8																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
(4) Force (lbs) @ 60%	4'	8.0	7.5	6.7																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
(5) Force (lbs) @ 80%	5'	8.2	8.3	9.6																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
(6) Force (lbs) @ 100%	6'	12.0	8.9	11.1																																																																																																										
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																										
			PASS																																																																																																											

# INTERTEK TEST DATA SHEETS

Page 5 of 9

Client:	Guardian Fall Protection	Engineer:	Andrew Rulison
Job No.:	G102531900	Tested By:	Andrew Rulison
Product:	Self-Retracting Lanyard	Reviewed By:	Jason Allen
Model No.:	10915	Standard:	ANSI/ASSE Z359.14-2014
Sample C/N:	See Table	<b>TRANSCRIBED TEST DATA</b>	

Section (Test)	Requirement	Results	Compliance																																																																																																												
3.1.9 (4.2.8.2)	<p><b>Dynamic Performance: “COLD”</b></p> <ol style="list-style-type: none"><li>connect 282 lb. weight</li><li>extract enough line for a 36-inch free fall per Fig 5 in Test Standard.</li><li>release the test weight</li><li>test within 90 seconds of removing from conditioning</li></ol> <table><tr><td>-40 C</td><td>Sample: 10</td><td>Sample: 11</td><td>Sample: 12</td></tr><tr><td>Conditioning in: (2 hrs min)</td><td>10:45 am</td><td>10:45 am</td><td>10:45 am</td></tr><tr><td>Conditioning out:</td><td>3:10 pm</td><td>3:15 pm</td><td>3:25 pm</td></tr><tr><td>Payout and retract the line per 3.1.6 following test</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Lock function shall operate per 3.1.2</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Visual indicator shall activate</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Max. Arrest Force: (lbs.) Class A &amp; B &lt; 1,800 lbs.</td><td>1225</td><td>1152</td><td>893</td></tr><tr><td>Avg Arrest Force (lbs.): Class A &lt; 1,575 lbs. Class B &lt; 1,125 lbs.</td><td>740</td><td>857</td><td>714</td></tr><tr><td>Distance Initial (in): D1</td><td>36”</td><td>36”</td><td>36”</td></tr><tr><td>Distance Final (in): D2</td><td>69”</td><td>65 ½ “</td><td>61 ½ “</td></tr><tr><td>Arrest Distance (in): D2-D1 Class A &lt; 24-inches Class B &lt; 54-inches</td><td>33”</td><td>29 ½ “</td><td>25 ½ “</td></tr></table> <table><tr><td>Section 3.1.6: Results of Retraction Testing following DP testing</td><td>Line Extension ( in or cm )</td><td>Sample: 3.1.5 A (#1)</td><td>Sample: 3.1.5 A (#2)</td><td>Sample: 3.1.5 A (#3)</td></tr><tr><td>(1) Force (lbs) @ 1 ft</td><td>1’</td><td>2.4</td><td>2.5</td><td>2.5</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(2) Force (lbs) @ 20%</td><td>2’</td><td>3.6</td><td>2.6</td><td>3.2</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(3) Force (lbs) @ 40%</td><td>3’</td><td>4.0</td><td>5.0</td><td>5.1</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(4) Force (lbs) @ 60%</td><td>4’</td><td>6.7</td><td>7.4</td><td>8.6</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(5) Force (lbs) @ 80%</td><td>5’</td><td>9.4</td><td>10.2</td><td>9.8</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(6) Force (lbs) @ 100%</td><td>6’</td><td>10.3</td><td>10.9</td><td>10.2</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr></table>	-40 C	Sample: 10	Sample: 11	Sample: 12	Conditioning in: (2 hrs min)	10:45 am	10:45 am	10:45 am	Conditioning out:	3:10 pm	3:15 pm	3:25 pm	Payout and retract the line per 3.1.6 following test	YES	YES	YES	Lock function shall operate per 3.1.2	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	1225	1152	893	Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	740	857	714	Distance Initial (in): D1	36”	36”	36”	Distance Final (in): D2	69”	65 ½ “	61 ½ “	Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	33”	29 ½ “	25 ½ “	Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)	(1) Force (lbs) @ 1 ft	1’	2.4	2.5	2.5	Retracted length < 24-inches		N/A	N/A	N/A	(2) Force (lbs) @ 20%	2’	3.6	2.6	3.2	Retracted length < 24-inches		N/A	N/A	N/A	(3) Force (lbs) @ 40%	3’	4.0	5.0	5.1	Retracted length < 24-inches		N/A	N/A	N/A	(4) Force (lbs) @ 60%	4’	6.7	7.4	8.6	Retracted length < 24-inches		N/A	N/A	N/A	(5) Force (lbs) @ 80%	5’	9.4	10.2	9.8	Retracted length < 24-inches		N/A	N/A	N/A	(6) Force (lbs) @ 100%	6’	10.3	10.9	10.2	Retracted length < 24-inches		N/A	N/A	N/A	<p><b>PASS</b></p>
-40 C	Sample: 10	Sample: 11	Sample: 12																																																																																																												
Conditioning in: (2 hrs min)	10:45 am	10:45 am	10:45 am																																																																																																												
Conditioning out:	3:10 pm	3:15 pm	3:25 pm																																																																																																												
Payout and retract the line per 3.1.6 following test	YES	YES	YES																																																																																																												
Lock function shall operate per 3.1.2	YES	YES	YES																																																																																																												
Visual indicator shall activate	YES	YES	YES																																																																																																												
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	1225	1152	893																																																																																																												
Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	740	857	714																																																																																																												
Distance Initial (in): D1	36”	36”	36”																																																																																																												
Distance Final (in): D2	69”	65 ½ “	61 ½ “																																																																																																												
Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	33”	29 ½ “	25 ½ “																																																																																																												
Section 3.1.6: Results of Retraction Testing following DP testing	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)																																																																																																											
(1) Force (lbs) @ 1 ft	1’	2.4	2.5	2.5																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(2) Force (lbs) @ 20%	2’	3.6	2.6	3.2																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(3) Force (lbs) @ 40%	3’	4.0	5.0	5.1																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(4) Force (lbs) @ 60%	4’	6.7	7.4	8.6																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(5) Force (lbs) @ 80%	5’	9.4	10.2	9.8																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(6) Force (lbs) @ 100%	6’	10.3	10.9	10.2																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											

# INTERTEK TEST DATA SHEETS

Page 6 of 9

Client:	Guardian Fall Protection	Engineer:	Andrew Rulison		
Job No.:	G102531900	Tested By:	Andrew Rulison	Date:	5/4/16
Product:	Self-Retracting Lanyard	Reviewed By:	Jason Allen	Date:	5/6/16
Model No.:	10915	Standard:	ANSI/ASSE Z359.14-2014		
Sample C/N:	See Table	<b>TRANSCRIBED TEST DATA</b>			

Section (Test)	Requirement	Results	Compliance																																																																																																												
3.1.9 (4.2.8.3)	<p><b>Dynamic Performance: “WET”</b></p> <ol style="list-style-type: none"><li>connect 282 lb. weight</li><li>extract enough line for a 36-inch free fall per Fig 5 in Test Standard.</li><li>release the test weight</li><li>test within 90 seconds of removing from conditioning</li></ol> <table><tr><td><b>Sample:</b></td><td>Sample: 13</td><td>Sample: 14</td><td>Sample: 15</td></tr><tr><td>Conditioning in: (2 hrs min)</td><td>12:30 pm</td><td>12:30 pm</td><td>12:30 pm</td></tr><tr><td>Conditioning out:</td><td>3:35 pm</td><td>3:41 pm</td><td>3:48pm</td></tr><tr><td>Payout and retract the line per 3.1.6 following test</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Lock function shall operate per 3.1.2</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Visual indicator shall activate</td><td>YES</td><td>YES</td><td>YES</td></tr><tr><td>Max. Arrest Force: (lbs.) Class A &amp; B &lt; 1,800 lbs.</td><td>765</td><td>1116</td><td>817</td></tr><tr><td>Avg Arrest Force (lbs.): Class A &lt; 1,575 lbs. Class B &lt; 1,125 lbs.</td><td>598</td><td>715</td><td>560</td></tr><tr><td>Distance Initial (in): D1</td><td>36”</td><td>36”</td><td>36”</td></tr><tr><td>Distance Final (in): D2</td><td>84 ½ “</td><td>65”</td><td>84”</td></tr><tr><td>Arrest Distance (in): D2-D1 Class A &lt; 24-inches Class B &lt; 54-inches</td><td>48 ½ “</td><td>29”</td><td>48”</td></tr></table> <table><tr><td></td><td>Line Extension ( in or cm )</td><td>Sample: 3.1.5 A (#1)</td><td>Sample: 3.1.5 A (#2)</td><td>Sample: 3.1.5 A (#3)</td></tr><tr><td>(1) Force (lbs) @ 1 ft</td><td>1'</td><td>2.0</td><td>1.9</td><td>2.5</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(2) Force (lbs) @ 20%</td><td>2'</td><td>3.0</td><td>3.7</td><td>2.8</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(3) Force (lbs) @ 40%</td><td>3'</td><td>4.4</td><td>5.4</td><td>4.6</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(4) Force (lbs) @ 60%</td><td>4'</td><td>7.3</td><td>6.7</td><td>7.2</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(5) Force (lbs) @ 80%</td><td>5'</td><td>10.2</td><td>8.5</td><td>8.1</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr><tr><td>(6) Force (lbs) @ 100%</td><td>6'</td><td>11.1</td><td>10.0</td><td>9.9</td></tr><tr><td>Retracted length &lt; 24-inches</td><td></td><td>N/A</td><td>N/A</td><td>N/A</td></tr></table>	<b>Sample:</b>	Sample: 13	Sample: 14	Sample: 15	Conditioning in: (2 hrs min)	12:30 pm	12:30 pm	12:30 pm	Conditioning out:	3:35 pm	3:41 pm	3:48pm	Payout and retract the line per 3.1.6 following test	YES	YES	YES	Lock function shall operate per 3.1.2	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	765	1116	817	Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	598	715	560	Distance Initial (in): D1	36”	36”	36”	Distance Final (in): D2	84 ½ “	65”	84”	Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	48 ½ “	29”	48”		Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)	(1) Force (lbs) @ 1 ft	1'	2.0	1.9	2.5	Retracted length < 24-inches		N/A	N/A	N/A	(2) Force (lbs) @ 20%	2'	3.0	3.7	2.8	Retracted length < 24-inches		N/A	N/A	N/A	(3) Force (lbs) @ 40%	3'	4.4	5.4	4.6	Retracted length < 24-inches		N/A	N/A	N/A	(4) Force (lbs) @ 60%	4'	7.3	6.7	7.2	Retracted length < 24-inches		N/A	N/A	N/A	(5) Force (lbs) @ 80%	5'	10.2	8.5	8.1	Retracted length < 24-inches		N/A	N/A	N/A	(6) Force (lbs) @ 100%	6'	11.1	10.0	9.9	Retracted length < 24-inches		N/A	N/A	N/A	<p><b>PASS</b></p>
<b>Sample:</b>	Sample: 13	Sample: 14	Sample: 15																																																																																																												
Conditioning in: (2 hrs min)	12:30 pm	12:30 pm	12:30 pm																																																																																																												
Conditioning out:	3:35 pm	3:41 pm	3:48pm																																																																																																												
Payout and retract the line per 3.1.6 following test	YES	YES	YES																																																																																																												
Lock function shall operate per 3.1.2	YES	YES	YES																																																																																																												
Visual indicator shall activate	YES	YES	YES																																																																																																												
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	765	1116	817																																																																																																												
Avg Arrest Force (lbs.): Class A < 1,575 lbs. Class B < 1,125 lbs.	598	715	560																																																																																																												
Distance Initial (in): D1	36”	36”	36”																																																																																																												
Distance Final (in): D2	84 ½ “	65”	84”																																																																																																												
Arrest Distance (in): D2-D1 Class A < 24-inches Class B < 54-inches	48 ½ “	29”	48”																																																																																																												
	Line Extension ( in or cm )	Sample: 3.1.5 A (#1)	Sample: 3.1.5 A (#2)	Sample: 3.1.5 A (#3)																																																																																																											
(1) Force (lbs) @ 1 ft	1'	2.0	1.9	2.5																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(2) Force (lbs) @ 20%	2'	3.0	3.7	2.8																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(3) Force (lbs) @ 40%	3'	4.4	5.4	4.6																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(4) Force (lbs) @ 60%	4'	7.3	6.7	7.2																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(5) Force (lbs) @ 80%	5'	10.2	8.5	8.1																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											
(6) Force (lbs) @ 100%	6'	11.1	10.0	9.9																																																																																																											
Retracted length < 24-inches		N/A	N/A	N/A																																																																																																											

# INTERTEK TEST DATA SHEETS

Page 7 of 9

Client: Guardian Fall Protection Engineer: Andrew Rulison  
Job No.: G102531900 Tested By: Andrew Rulison Date: 5/4/16  
Product: Self-Retracting Lanyard Reviewed By: Jason Allen Date: 5/6/16  
Model No.: 10915 Standard: ANSI/ASSE Z359.14-2014  
Sample C/N: See Table **TRANSCRIBED TEST DATA**

Section (Test)	Requirement	Results				Compliance
3	Requirements					
3.1	General Requirements					
3.1.1	Integral Connectors- shall meet the requirements of ANSI/ASSE Z359.12		YES			PASS
3.1.2	Locking Function- shall be automatic in there locking function. It shall not be possible to override the features.		YES			PASS
3.1.3	Energy Absorption-		NO			NA
3.1.4	Visual Indicator-	See section 3.1.9 for results				PASS
3.3.1	Synthetic Rope		NO			NA
5	“Marking and Instructions”					
5.1.1	Shall be in English					PASS
5.1.3	Self-Retracting Devices shall be marked with the following:					PASS
	Marking	Comments	YES	NO	NA	
	Part number and model designation		X			
	Year of manufacture		X			
	Manufacturer's name or logo		X			
	Capacity Range		X			
	Unique ID Number		X			
	Standard Number (Z359.14)		X			
	How to inspect the visual indicator		X			
	Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X			
	Warning of the need for inspection in accordance with the manufacturer's instructions		X			
	The fiber or other materials used in the lanyard construction		X			
	The lanyard working length		X			
	Average arresting force for the SRD class		X			
	Arresting distance		X			
	Proper installation means		X			
	Warning on the need for testing the device for locking and retraction before each use		X			
	SRD class and arrest distance		X			
	Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X			
	Free fall limit		X			
	Suitability for use with horizontal lifelines		X			
	Suitability for horizontal use		X			
5.2.1	Instructions shall be in English, and affixed to the equipment at time of shipment from the manufacturer					PASS

# INTERTEK TEST DATA SHEETS

Page 8 of 9

Client: Guardian Fall Protection Engineer: Andrew Rulison  
 Job No.: G102531900 Tested By: Andrew Rulison Date: 5/4/16  
 Product: Self-Retracting Lanyard Reviewed By: Jason Allen Date: 5/6/16  
 Model No.: 10915 Standard: ANSI/ASSE Z359.14-2014  
 Sample C/N: See Table **TRANSCRIBED TEST DATA**

Section (Test)	Requirement	Results				Compliance
5.2.2	<b>Instructions shall contain the following information:</b>					<b>PASS</b>
	Instructions	Comments	YES	NO	NA	
	A statement that the manufacturer's instructions shall be provided to the users		X			
	Manufacturers name, address, and telephone number		X			
	Manufacturer's part number and model designation for the equipment		X			
	Intended use and purpose of the equipment		X			
	Proper method of use and limitations on use of the equipment		X			
	Illustrations showing locations of markings on the equipment		X			
	Reproduction of printed information on all markings		X			
	Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X			
	Anchorage requirements		X			
	Criteria for discarding equipment which fails inspection		X			
	Procedures for cleaning, maintenance, and storage		X			
	Reference to Z359 standards		X			
	Proper installation means and limitations on the type of anchorage connectors used		X			
	The fiber or other materials used in the lanyard construction		X			
	The lanyard length		X			
	The average arresting force when dynamically tested in accordance with the requirements of the standard		X			
	SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X			
	How to determine fall clearance		X			
Testing the device for locking before each use		X				
5.2.3	Instructions shall require that only the equipment manufacturer , or persons or entities authorized in writing by the manufacturer, shall make repairs to the equipment					<b>PASS</b>
5.2.4	Instructions shall require the user to remove equipment from service if it has been subjected to the forces of arresting a fall or affecting a rescue					<b>PASS</b>
5.2.5	Instructions shall require the user to have a written rescue plan and the means at hand to implement it when using the equipment					<b>PASS</b>



# INTERTEK TEST DATA SHEETS

Page 9 of 9

Client:	Guardian Fall Protection	Engineer:	Andrew Rulison
Job No.:	G102531900	Tested By:	Andrew Rulison
Product:	Self-Retracting Lanyard	Reviewed By:	Jason Allen
Model No.:	10915	Standard:	ANSI/ASSE Z359.14-2014
Sample C/N:	See Table	TRANSCRIBED TEST DATA	

Section (Test)	Requirement	Results				Compliance
5.2.6	Instructions shall provide warnings regarding:					PASS
	Warnings	Comments	YES	NO	NA	
	Altering the equipment		X			
	Misusing the equipment		X			
	Using combinations of components or sub-systems, or both, which may affect or interfere with the safe function of each other		X			
	Exposing the equipment to chemicals, high heat, severe cold, or other harsh environments which may produce a harmful effect and to consult the manufacturer in case of doubt		X			
	Using the equipment around moving machinery and electrical hazards		X			
	Using the equipment near sharp edges or abrasive surfaces		X			
	Risk of striking an object or obstruction during a swing fall		X			
	That the consequences of improperly using the device, not following instructions or markings may cause serious injury or death		X			

## Testing Pictures

