Recycled

Recyclable

MSDS 4800DW Revision No. 009

September 22, 2014 Date of Issue





MATERIAL SAFETY DATA SHEET

Product Identifier Firestop 4800DW

Fire and Smoke Stop Caulk and Sealant **Product Use**

Manufacturer Passive Fire Protection Partners, 1412 Derwent Way, Delta, BC V3M 6H9

Emergency Number (800) 810 - 1788

INGREDIENT INFORMATION									
Ingredient Calcuim Carbonate	CAS # 1317-65-3	% (wt.) < 50	LC ₅₀ (rat) N/A	LD₅₀ (rat) N/A	TLV N/A	STEL N/E			
Vinyl Acetate Polymers	Not disclosed	< 40	N/A	N/A	N/A	N/A			
Water	7732-18-5	< 25	N/A	N/A	N/E	N/E			
Auxiliary Chemicals	N/A	< 5	N/A	N/A	N/A	N/A			
Iron Red Oxide(1)	1309-37-1	< 0.5	N/A	N/A	N/A	N/A			
Iron BlackOxide(2)	1317-61-9	< 0.1	N/A	N/A	N/A	N/A			
Titanium Dioxide(2),(3)	13463-67-7	< 1	N/A	N/A	10 mg/m ³	N/A			
Iron Yellow Oxide(4)	51274-00-1	< 0.5	N/A	N/A	N/A	N/A			
Aqueous Colorant, Blue(5)	N/A	< 0.5	N/A	N/A	N/A	N/A			

(1) - Red; (2) - Grey; (3) - White; (4) - Yellow; (5) - Blue

PHYSICAL PROPERTIES

Red, viscous compound	Specific Gravity (@25°C)	1.40 – 1.50				
Mild odour	Evaporation Rate	< 1				
Slight aromatic ordour	Boiling Point (°C)	> 100				
18.51880	Freezing Point (°C)	0				
of water vapor	рН	8 - 9				
Not determined	VOC contents (g/L)	32.5				
	Red, viscous compound Mild odour Slight aromatic ordour 18.51880 of water vapor	Red, viscous compound Mild odour Slight aromatic ordour 18.51880 of water vapor Specific Gravity (@25°C) Evaporation Rate Boiling Point (°C) Freezing Point (°C) pH				

		N DATA

Flammability No

Means of Extinction Normal fire fighting procedures should be followed to avoid inhalation of

smokes and gases.

Special Fire-fighting Procedures Firefighters should wear the usual protective gear use self-contained

breathing apparatus.

N/A **Auto-ignition Temperature (°C)** Flash Point (°C) / Method N/A **Upper Flammable Limit (%, Vol.)** N/A Lower Flammable Limit (%, Vol.) N/A **Sensitivity to Mechanical Impact** No Sensitivity to Static Discharge No

Hazardous Combustion Products Carbon Monoxide and/or Carbon Dioxide



1.800.810.1788 Technical Support 1.800.810.1788 Customer Service www.firestop.com email: firestop@firestop.com



MSDS 4800DW Revision No. 009

September 22, 2014 Date of Issue

2 of 3

Page

MSDS - 4800DW

REACTIVITY DATA **Stability** Stable at normal condition

Condition of Reactivity Contact with incompatible substances

Incompatible Materials Reacts with strong acids and liberates carbon dioxide

Hazardous Decomposition Dried film forced to burn will produce: Carbon Monoxide, Carbon Dioxide,

Products and Hydrocarbon Oxidation products.

TOXICOLOGICAL PROPERTIES

Routes of Exposure Skin □ Skin □ Eye contact □ Inhalation

> contact absorption

Effects of Acute Exposure to

Product

Skin and eyes irritation may occur after contact with the product.

Effects of Chronic Exposure to

Product

None known

Exposure Limits None known

Irritancy of Product Slight on skin and eyes

Sensitization of Product None known Carcinogenicity None known **Teratogenicity** None known Reproductive Toxicity None known

FIRST AID MEASURES

Eye Contact Flush with large quantites of water gently for 15 minutes and get

immediate medical attention.

Skin Contact Wash with soap and water immediately

Inhalation Remove affected person away from source of exposure to fresh air and

get medical attention IMMEDIATELY.

Ingestion Get medical attention IMMEDIATELY.

PREVENTIVE MEASURES

General ventilation is recommended during normal use. . **Engineering Controls**

Personal Protective Equipment Not generally during normal use and handling.

Eye Protection (Specify) Face shield or chemical goggles were recommended.

Skin Protection (Specify) Chemical resistant nitrile, neoprene or rubber gloves were recommended

if contact to the product directly.

Respiratory (Specify) Respiratory was recommended if the product was installed in poorly

ventilated areas.

Other

Recycled

Recyclable

PRECAUTION FOR SAFE HANDLING AND USE

Handling Procedure and N/A

Equipment

Material should be kept in a closed container stored between 4 - 32°C Storage Requirement

(40 - 90°F).

Spill, Leak or Releases Wear protective equipment during cleanup.

Waste Disposal Care should be taken to ensure that the material or its containers

and disposed of in an approved facility, state, provincial and local

environmental control regulations.

Special Shipping Instructions DO NOT FREEZE



Recycled

Recyclable

MSDS 4800DW 009 Revision No.

Date of Issue September 22, 2014





REGULATION INFORMATION

WHMIS Not controlled

HMIS Health 1, Flammability 0, Reactivity 0 **TDG Regulation** Not classified as a hazardous material

TSCA All ingredients of this product are on the inventory list.

DSL All ingredients of this product are on the list.

PREPARATION INFORMATION

Prepared by Chemical Laboratory, Passive Fire Protection Partners

Date of Issue June 13, 2001 (604) 515-1788 **Telephone** Website www.firestop.com

Reason for Revision New formulation, rev 001, March 22, 2002

New format MSDS, rev 002, September 16, 2004

Ingredient information updating, rev 003, November 10. 2006

MSDS reviewing, rev 004, December 30, 2008 Formulation updating, rev 005, August 24, 2009

Spelling mistake on Section of Precaution for Safe Handling and Use,

rev 006, March 1, 2010

Formulation updating, rev 007, January 3, 2011 MSDS format change, rev 008, September 24, 2012

Revision Date September 22, 2014

Abbreviations Used % (wt.) = Weight Percentage

ACGIH = American Conference of Governmental Industrial Hygienists

CAS Number = Chemical Abstracts Series Number

DSL = Domestic Substance List in Canada

H = Hours

HMIS = Hazardous Material Identification System IARC = International Agency for Research on Cancer

LC₅₀ = Lethal Concentration, 50%

LD₅₀ = Lethal Dose, 50%

MSHA = Mine Safety and Health Administration

N/A = Not Applicable or Not Available

N/E = None Established

NIOSH = The National Institute for Occupational Safety and Health

NTG = National Toxicology Program

OSHA = The Occupational Safety and Administration

STEL = Short Term Exposure Limit

TDG = Transportation of Dangerous Goods

TLV = Threshould Limit Value

TSCA = Toxic Substance Control Act in US

VOC = Volatile Organic Compounds

WHMIS = Workplace Hazardous Material Identification System

This information is provided in good faith and is correct to the best of PFP Partners' knowledge as of the date hereof; however, PFP Partners makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. PFP Partners disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS. EXPRESS OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.



1.800.810.1788 Technical Support 1.800.810.1788 Customer Service

www.firestop.com email: firestop@firestop.com