



Revision Number: 009.0

Issue date: 11/08/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE SI 5900 INSTANT GASKET MAKER known as 5900 Flange Sealant	IDH number:	212184
Product type:	Silicone	Item number:	20166
Restriction of Use:	None identified	Region:	Canada
Company address:	Contact information:		
Henkel Canada Corporation	Telephone: (905) 814-6511		
2515 Meadowpine Boulevard	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 212184

Product name: LOCTITE SI 5900 INSTANT GASKET MAKER known as 5900 Flange Sealant

Hazardous Component(s)	CAS Number	Weight %*
Calcium carbonate	471-34-1	40 - 50
Butan-2-one O,O',O''-(vinylsilyldyne)trioxime	2224-33-1	1 - 5
Carbon black	1333-86-4	1 - 5
Aluminum	7429-90-5	0.1 - 1
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	34206-40-1	0.1 - 1
3-(Trimethoxysilyl)propylamine	13822-56-5	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Methyl ethyl ketoxime is formed during cure.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms develop and persist, get medical attention.
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self contained breathing apparatus. Prevent inhalation of fumes and gases.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of silicon. Formaldehyde. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Do not wear contact lenses.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium carbonate	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Butan-2-one O,O',O''-(vinylsilyldiene)trioxime	None	None	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction.	None	None
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	None	None	None	None
3-(Trimethoxysilyl)propylamine	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use a dust mask for particulate concentrations exceeding the Occupational Exposure Limit. Use an organic vapor respirator for concentrations exceeding the Occupational Exposure Limit.

Eye/face protection: Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

Skin protection: Permeation resistant gloves (butyl rubber, nitrile rubber, polyvinyl alcohol).

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor:	Mild
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	< 5 mm hg (20 °C (68°F))
Boiling point/range:	Not applicable
Melting point/ range:	Not available.
Specific gravity:	1.31 at 20 °C (68°F)
Vapor density:	Heavier than air.
Flash point:	> 93 °C (> 199.4 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Polymerises in presence of water.

Partition coefficient (n-octanol/water): Not available.
VOC content: 3.31 %; 44.47 g/l
Viscosity: Not available.
Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Hazardous reactions: None under normal processing.
Hazardous decomposition products: Methyl ethyl ketoxime formed during cure. Oxides of carbon. Oxides of silicon. Formaldehyde.
Incompatible materials: Acids and bases. Oxidizing agents. Polymerizes on contact with water.
Reactivity: Not available.
Conditions to avoid: Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Skin contact: Prolonged or repeated contact with uncured sealant may cause skin irritation. May cause allergic skin reaction.
Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion: Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg	Nuisance dust
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime	None	Irritant, Allergen
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity
Aluminum	None	Central nervous system, Irritant, Lung
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	None	Irritant, Allergen
3-(Trimethoxysilyl)propylamine	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcium carbonate	No	No	No
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime	No	No	No
Carbon black	No	Group 2B	No
Aluminum	No	No	No
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	No	No	No
3-(Trimethoxysilyl)propylamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured rubber can be incinerated or landfilled following EPA and local regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Exceptions:	None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Timothy Pratt, Regulatory Affairs Specialist

Issue date: 11/08/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.